



YHM MESH WIRE IN COIL
(Cold Reduced Steel Wire for The Reinforcement of Concrete)

1.0 Specification

Product Code	Nominal Size (mm)	Wire Type	Cross-sectional Area (mm ²)	Mass per Meter Run (kg/m)	Inner Coil Diameter (mm)	Weight per Coil (kg)
YHM-R2.0	2.0	Round	3.1	0.025	400	500 / 750
YHM-R2.2	2.2	Round	3.8	0.030	400	500 / 750
YHM-R2.4	2.4	Round	4.5	0.035	400	500 / 750
YHM-R2.6	2.6	Round	5.3	0.042	400	500 / 750
YHM-R2.8	2.8	Round	6.2	0.048	400	500 / 750
YHM-R3.0	3.0	Round	7.1	0.055	400	500 / 750
YHM-R3.2	3.2	Round	8.0	0.063	400	500 / 750
YHM-R3.4	3.4	Round	9.1	0.071	400	500 / 750
YHM-R3.6	3.6	Round	10.2	0.080	400	500 / 750
YHM-R3.8	3.8	Round	11.3	0.089	400	500 / 750
YHM-R4.0	4.0	Round	12.6	0.099	400	500 / 750

Note:

- 1.1 YHM Mesh Wire is a non stock item. Produced only upon request.
- 1.2 Cross-sectional area and mass per meter run are subject to the tolerance of $\pm 4\%$ of their nominal values respectively.
- 1.3 Output of coil is in spool form with specified inner diameter. Outer diameter is 1000 mm maximum.
- 1.4 The weight of coil is subject to the tolerance of ± 20 kg.
- 1.5 The minimum yield strength is 485 N/mm². Minimum tensile strength shall be 2% greater than actual yield strength.

2.0 List Price per Metric Ton

Size (mm)	RM	Min. Order Quantity (MT)
< 5	5000	5

Note:

- 1.1 YHM Mesh Wire is a non stock item. Produced only upon request.
- 1.2 Cross-sectional area and mass per meter run are subject to the tolerance of $\pm 4\%$ of their nominal values respectively.
- 1.3 Output of coil is in spool form with specified inner diameter. Outer diameter is 1000 mm maximum.
- 1.4 The weight of coil is subject to the tolerance of ± 20 kg.